

TopEfekt[®] TOTAL

Technical Data Sheet



SYMBOL	pH
P-05	14

Alkaline product, designed for removing old and worn out polymer coatings. Really useful for removing piled up wax and soap layers. Quickly dissolves any kind of coating. Low-foaming, does not harm cleaned surfaces and may be also used for thorough cleaning of the floors.

APPLICATION:

- delicate surfaces, linoleum, enamelled floors, limey stone
- hard surfaces resistant to water and alkaline substances

COMPOSITION:

- < 7% sodium hydroxide
- < 5% phosphonates
- < 5% anionic surfactants
- < 5% non-ionic surfactants
- auxiliary substances not classified as dangerous

USAGE:

Read product's safety data sheet before using.

- delicate floors: 0.5-1 l / 10 l of water
- others: 1-3 l / 10 l of water

Washed surfaces must be neutralized with water

TopEfekt[®] TOTAL

Technical Data Sheet

DANGER:



- Causes severe skin burns and eye damage.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER/doctor
- Store locked up.

SELL-BY DATE:

36 months from the production date.

Production date/series and expiration date are stated on the packaging.

ADDITIONAL INFORMATION:

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations