

## TopEfekt® DIAM

### Technical Data Sheet



SYMBOL	pH
P-03	8.5

Washing-nurturing product, designed for cleaning stone and elastic hard floors (preserved and unpreserved). Low-foaming product, based on wax emulsions. Has anti-slip, anti-reflective and antistatic properties. Refills and renews polymer layers. Everyday cleaning gives lightening effect. Does not leave any stains. Protects the floor and hinders renewed dirt settling. Suitable for polishing surfaces.

#### **APPLICATION:**

- polymer protected floors
- ceramic tiles, stone, PVC, varnished wood, clinker, rubber, linoleum
- public facilities, sport floors
- floors with slipping risk

#### **COMPOSITION:**

- < 5% anionic surfactants
- < 5% non-ionic surfactants
- aroma composition
- auxiliary substances not classified as dangerous

#### **USAGE:**

Read product's safety data sheet before using.

- mechanical cleaning: 50-100 ml / 10 l of water
- manual cleaning unpreserved floors: 25-50 ml / 10 l of water
- preserved floors: 25 l / 10 l of water

## *TopEfekt<sup>®</sup> DIAM*

### **Technical Data Sheet**

Does not need to be washed down with water.

#### **DANGER:**



- Causes serious eye irritation.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### **SELL-BY DATE:**

36 months from the production date.

Production date/series and expiration date are stated on the packaging.

#### **ADDITIONAL INFORMATION:**

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations