

TENZI

Advantage through quality

**HYGIENE PRODUCTS FOR
INDUSTRIAL FACILITIES**
FLOORS, WALLS, MACHINES
AND TOOLS



**25 YEARS
ANNIVERSARY**

PRODUCTS FOR FLOOR DEEP CLEANING

SUPER GREEN SPECIAL NF CONCENTRATE

REMOVAL OF PETROLEUM CONTAMINATION FROM INDUSTRIAL FLOORS

Low-foaming, alkaline product with wide range of use. Recommended for cleaning strongly polluted, neglected industrial floors with petroleum contaminations. Very effective in repair workshops and in heavy industry. Use with cold water

APPLICATION AREA:

- automotive industry
- tools industry
- car services
- machine
- equipments
- production halls

METHOD OF USE:

depending on the contamination level of the surface:

- daily cleaning: 50-200 ml / 10 l of water
- deep cleaning: 500-1000 ml / 10 l of water.

When cleaning the surface by spraying, use at least 5% solution.

Warning: Rinsing the surface with clean water will slow down resoiling

1L - 11005A001
5L - 11005A005
10L - 11005A010
20L - 11005A020
200L - 11005A200



RONAL CONCENTRATE

CLEANING STRONGLY STONE FLOORS AND INDUSTRIAL

Alkaline product with wide range of use, recommended for cleaning strongly polluted industrial and stone floors (natural and artificial). Removes all kinds of oily, greasy and sooty contaminations. It's very intense on porous stone tiles. Does not leave any stains.

APPLICATION AREA:

- electrical machine industry
- logistic centers
- underground garages
- productions halls (floors, walls)
- arms industry
- operational and petroleum dirt

METHOD OF USE:

- daily washing: 50-100 ml / 10 l of water
- thorough cleaning: 200-500 ml / 10 l of water

Warning: rinsing the surface with clean water will slow down process of resoiling

1L - 11002A001
10L - 11002A010



PRODUCT FOR **CLEANING THE FACADE**

APC OUT **CONCENTRATE**

EXTERNAL SURFACE, CLEANING TOUGH DIRT

Extremely effective alkaline product for cleaning: facade, roofs, organic dirt (plants, bugs, rotten process) petroleum pollution (grease, oils, coolant)

APPLICATION AREA:

- facades
- elevations
- roofs
- siding
- exterior panels
- ceramic and tin roof tiles
- external surfaces of industrial facilities

METHOD OF USE:

- use as water solution according to the level of surface contamination
- diluted 1:1 to 1:10 with water
- spread the product on to washed surface by sprinkler or foaming
- wash it down with high pressure (around 100bar)

Attention: use of warm water 40-60°C will significantly improve the cleaning result

1L - PP012A001
5L - PP012A005

**LEADER
OF
EFFECTIVENES
ON THE MARKET
FOR 10 YEARS**



WASHING, DISINFECTION, LIME SCALE AND RUST REMOVAL

GRAN CLOR® 2006 CONCENTRATE

DEGREASING AND DISINFECTING ROOMS WITH ROTTEN PROCESS, MOULD AND FUNGIES

Highly alkaline product for washing-disinfecting sanitary surfaces, machines, equipments and surface which have direct contact with food. It contains an active chlorine. Degreases and removes strong dirt of plant and animals origin created in rotten process. Attested by National Institute of Public Health.

APPLICATION AREA:

- food processing (meat, fish, poultry - containers)
- slaughterhouse
- recycling centers, rubbish transport
- isotherms
- water works facilities, sewage system

METHOD OF USE:

- disinfecting in 20°C
- general disinfecting: concentration 200 ml / 10l of water, working time : 15 minutes
- pittings - 200 ml / 10l of water, working time 15 minutes
- bacteries - 100 ml / 10l of water, working time 5 minutes
- fungies - 40 ml / 10l of water, working time 15 minutes
- viruses - 100 ml / 10l of water working time 10 minutes
- at the end rinse the surface with clean water
- working solution has to be done just before the application

1L - SP023A001
5L - SP023A005
10L - SP023A010
20L - SP023A020



DERAST® CONCENTRATE

REMOVING MINERAL ORIGIN DIRT

Highly acidic product, removes limescale, limestone and rust from surfaces resistant to acids. Contains hydrochloric acid.

APPLICATION AREA:

- surfaces with high humidity,
- building industry (machines, devices)

METHOD OF USE:

- machine cleaning: 100 - 200 ml / 10 l of water,
 - manual cleaning: 300 - 600 ml / 10 l of water,
- after use, wash the surface with highly pressured water,
- Floors, walls: 100 - 200 ml / 10 l of water,
 - toilet bowls and urinals: 1l / 10 l of water,
- Boilers: 1:3 with water, reaction time 10-15 min.
- After cleaning, wash the surface with water.

Warning: Do not use on enameled surface or ceramic armature. Do not let it dry. Sensitive places such as grouts should be soaked with water before using the product.

1L - TT002A001
10L - TT002A010



PRODUCT FOR THOROUGH AND DAILY CLEANING

TopEpekt® STR CONCENTRATE

THOROUGH CLEANING OF ELASTIC SURFACES

Low foaming, alkaline product, designed for mechanical and manual cleaning of strongly contaminated industrial floors. Dissolves impurities of greasy and oily origin. May be used as a stain remover for greasy stains on carpet floorings. Recommended for cleaning elastic surfaces such as PVC, linoleum, vinyl, resinous carpets etc.

APPLICATION AREA:

- wholesale stores
- painted floors
- PCV
- warehouses

METHOD OF USE:

- manual cleaning: 100-200 ml / 10 l of water
 - mechanical cleaning: 100-300 ml / 10 l of water
 - thorough cleaning: 200-500 ml / 10 l of water
- 1L - II001A001
10L - II001A010



TOPEFEKT® CONTRA CONCENTRATE

THOROUGH CLEANING OFFLOORING IN SUPERMARKETS

A low-foaming, intensive alkaline product with a wide range of applications. Recommended for thorough cleaning of all heavily contaminated industrial floors with a floor cleaning machine. Does not leave streaks. Perfectly dissolves most polymer coatings from alkali-resistant floors.



APPLICATION AREA:

- supermarkets
- warehouses
- large wholesale stores

METHOD OF USE:

- machine washing: 50-200 ml / 10 l of water
- removing old polymer coatings 1-3/10 liters of water
- additional cleaning 200-500 ml / 10 liters of water
- final rinsing with clean water slows down surface resoiling

10L - II004A010

PRODUCTS FOR DAILY CLEANING

BRUDEX CONCENTRATE

REMOVES OILY AND GREASY DIRT

All-purpose cleaning-degreasing product, designed for removing impurities of organic origin. Cleans, washes, degreases and removes stains at the same time. Recommended to keep hygiene for industrial and household conditions.

APPLICATION AREA:

- food processing
- gastronomy (floors, walls, washing work clothes)
- staircases
- corridors

METHOD OF USE:

Product designed for surfaces resistant for alkalines action.

Depending on the type of surface and its contamination level, it is recommended to use following solutions:

- cleaning, daily laundry: 10-50 ml / 10 l of water
- cleaning, thorough laundry: 100-500 ml / 10 l of water
- rinsing the surface with clean water will slow down process of resoiling

1L - UU006A001
5L - UU006A005
10L - UU006A010
200L - UU006A200

TOP PERFEKT CONCENTRATE

CLEANING SURFACES IN FOOD INDUSTRY

Low-foaming, smell free product with degreasing and cleaning properties for daily and thorough cleaning surfaces resistant to alkaline substances. Effectively dissolves old oily and greasy contaminations of floral and animal origin. Can be used with hard water. Recommended for all kinds of hard surfaces (stone, ceramic, elastic). Safe for the environment.

APPLICATION AREA:

- food industry
- gastronomy (floors, walls)
- staircases
- corridors

METHOD OF USE:

- thorough cleaning: 100-200 ml / 10 l of water
- Daily cleaning: 25-50 ml / 10 l of water
- in case of removing old, greasy contaminations, it is recommended to use 40°C warm water.
- rinsing the surface with clean water will slow down process of taking the dirt again

1L - II011A001
5L - II011A005
10L - II011A010



PRODUCTS FOR THOROUGH CLEANING

GRAN[®] SMOG **CONCENTRATE**

REMOVES OILY AND GREASY DIRT

Concentrated product designed for thoroughly cleaning grills, ovens, stoves, grates and fireplaces. Effectively removes scorched grease, oil and soot while leaving clean and shiny surface. Contains corrosion inhibitors, tolerates hard water. Removes post fire dirt from all types of surfaces

APPLICATION AREA:

- ovens
- stoves,
- grills
- fireplaces
- smoking chambers
- alkaline resistant floors

METHOD OF USE:

the best is to use foaming method.

- piled up hard grease: 3-4 l / 7-6 l of water
- post fire contaminations: 3-4 l / 7-6 l of water
- daily cleaning: 500-1000 ml / 9-10 l of water
- water temperature 40-60°C
- reaction time about 30 minutes
- wash down with clean, hot water and leave it to dry off.

1L - SP003A001
5L - SP003A005
10L - SP003A010
20L - SP003A020

RUBBER OFF **CONCENTRATE**

**REMOVING VULCANIZED RUBBER
FROM FLOORS**

Concentrated product designed for removing rubber traces from all kinds of hard surfaces. Excellently dissolves greasy exploitative dirt and adhesives used by athletes (paraffin and resinous).

APPLICATION AREA:

- corridors
- underground garages
- industrial floors
- production
- sports halls
- logistics centers
- pavement bricks

METHOD OF USE:

- daily cleaning: 0.5 - 2% (50 - 200 ml / 10 l of water)
- old dirt: 10 - 20% (1 - 2 l / 9-8 l of water)
- spot cleaning (layered dirt) 1:3 - 1:1 with water
- in extreme cases without dilution

Prepare a working solution depending on the level of dirt, apply it to the contaminated area and wait for 1-2 minutes. Scrub it mechanically or by hand, pick up all the dirt and wash the area with fresh water. Dry it yourself or allow it to dry off on its own.

1L - PP017A001
10L - PP015A010



PRODUCTS FOR DAILY CLEANING

TopEfekt® NORMAL CONCENTRATE

DAILY CLEANING OF THE FREQUENTLY AND FAST CONTAMINATED FLOORS

Low-foaming, slightly alkaline, all-purpose product with a pleasant scent. Removes intense pollution and does not rinse out washed surface, does not leave any stains. Hinders renewed dirt settling and may be used in scrubber dryers. Recommended for all kinds of surfaces that are exposed to frequent pollution.

APPLICATION AREA:

- Light electronic
- textile
- clothes industry
- public utility facilities (matt floors)

METHOD OF USE:

- manual cleaning: 25-50 ml / 10 l of water
- mechanical cleaning: 50-100 ml / 10 l of water.

Does not need to be washed down with water. Product is appropriate for using in scrubbing-drying machines.

1L - PP004A001
5L - PP004A005
10L - PP004A010
200L - PP004A200



TopEfekt® ORANŻ / CITRO / EXOTIC CONCENTRATE

DAILY CLEANING OF THE FLOORS AND INTERIOR FITTINGS

General purpose cleaner. Recommended for all glass like shiny surfaces, which have a low absorpency. Removes stubborn dirt. It has a pleasant scent (orange, lemon or exotic fruits).

APPLICATION AREA:

- light industry,
- electronic industry,
- textile industry
- clothing industry
- public facilities (glossy floors)

METHOD OF USE:

- sprayer: 2.5-5 ml / 1l of water
- manually: 25-50 ml / 10 l of water
- machine: 50-100 ml / 10 l of water
- does not require rinsing with water



TopEfekt® CITRO
1L - BB004A001
5L - BB004A005
10L - BB004A010

TopEfekt® ORANŻ
1L - BB001A001
5L - BB001A005
10L - BB001A010

TopEfekt® EXOTIC
1L - PP011A001
5L - PP011A005
10L - PP011A010

